



AU9718936

(12) PATENT ABSTRACT (11) Document No. AU-A-18936/97
(19) AUSTRALIAN PATENT OFFICE

(54) Title
METHOD AND DEVICE FOR CONNECTION BY INSULATION-DISPLACING CONTACTS

International Patent Classification(s)
(51)⁶ H01R 004/24 H01R 004/70 H01R 043/01

(21) Application No. : 18936/97 (22) Application Date : 17/04/97

(30) Priority Data

(31) Number (32) Date (33) Country
96420149 02/05/96 EP EUROPEAN PATENT OFFICE (EP)

(43) Publication Date : 06/11/97

(71) Applicant(s)
POUYET S.A.

(72) Inventor(s)
XAVIER FASCE

(74) Attorney or Agent
SHELSTON WATERS , Level 21, 60 Margaret Street, SYDNEY NSW 2000

(57)

This invention relates to a method and device for reliably and positively connecting electric wires in receiving insulation-displacing slots.

The pivoting connection pusher (4) is closed by a locking catch (7) borne by an elastic tongue (71) and cooperating with a fixed closure stop (8). Locking is produced after passage of a hard point and provokes a clearly audible click which indicates to the installer that the insulation-displacing connection of the wire (6) is then positively effected.

- 1 -

AUSTRALIA

PATENTS ACT 1990

COMPLETE SPECIFICATION

FOR A STANDARD PATENT

ORIGINAL

Name of Applicant/s: Pouyet S.A.

Actual Inventor/s: Xavier Fasce

Address of Service: SHELSTON WATERS
60 MARGARET STREET
SYDNEY NSW 2000

Invention Title: "METHOD AND DEVICE FOR CONNECTION BY
INSULATION-DISPLACING CONTACTS"

The following statement is a full description of this invention,
including the best method of performing it known to us:-

(File: 19613.00)

FIELD OF THE INVENTION

The present invention relates to a method and to a device for connection by insulation-displacing contacts.

BACKGROUND OF THE INVENTION

5 Rapid connections by contacts with insulation-displacing slots are now widely used in industry, in particular in the telephone- and computer-related connector technology industry.

10 US Patent No 5,358,430 describes a female socket of the modular jack type with connections integrated therein. The modular jack contacts of the front opening of this socket are taken up at the rear on two series of insulation-displacing contacts. The connection of a wrapped telephone wire at the rear of the socket is then effected, without a special tool, by closure of two respective rotating covers which serve, on
15 driving the wires in their respective receiving insulation-displacing slots, as rotating connection pushers.

This type of rotating pusher is very practical, but, in fact, it does not guarantee total operational reliability, as the installer is never absolutely certain that the connection
20 is made. Out of a very large number of connections that he must effect every day, it may very well be that, for some of them, the rotating pusher has in fact not undergone a sufficient rotation and that, consequently, the corresponding wires are not correctly connected.

25 It is an object of the invention to overcome this drawback.

SUMMARY OF THE INVENTION

To that end, the present invention relates to a method for connection of wrapped wires by driving these wires in receiving
30 insulation-displacing slots, by means of a rotating pusher of the pivoting cover type, characterized in that it consists in providing an elastic element which is fast with the rotating pusner and which is stretched during rotation of this pusher

for engagement of these wires in these slots, then which is suddenly released, at the end of stroke of this pusher, so that it violently hits the nose of a hard body which is prominent with respect to the means for holding the metallic contacts with insulation-displacing slots and which is fast with this means, so as to obtain a clearly audible click which indicates to the installer that the insulation-displacing connection is positively effected, and whose sound intensity is at least equal to 45 decibels A.

This violent shock is advantageously created by the closure of a catch for locking this pusher at the end of stroke, this catch being taut in open position before release, and locking at the moment of its violent shock at the end of stroke.

The invention also relates to a device for carrying out this method, this device being characterized in that said connection pusher is a rotating pusher of the pivoting cover type, which comprises an elastic end-of-stroke locking catch, this catch cooperating with a fixed end-of-stroke locking stop and this locking stop cooperating with this catch to create a hard point of passage corresponding to a maximum tension of said catch and suddenly to release this catch in position of locking against the locking stop immediately after passage of this hard point, the sudden shock of the catch against its receiving part then producing said audible click.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention will be more readily understood on reading the following description with reference to the accompanying drawings, in which:

Figure 1 is a view in perspective of the rear part of a telephone or computer socket, this rear part forming a device for connecting, by insulation-displacing contacts, telephone or

computer lines with a wire ready to be connected and the connection pusher in open position.

Figures 2 to 4 show, in partial longitudinal section along IV-IV of Figure 5, the successive phases of connection of this wire.

Figure 5 is a view in horizontal section along V-V of Figure 4.

DESCRIPTION OF PREFERRED EMBODIMENT

Referring now to the drawings, Figure 1 shows the rear part of a monopair modular jack socket. This socket comprises two insulation-displacing metallic contacts 1, 2 which, in this embodiment, each comprise two insulation-displacing slots, as is the case for those described in US Patent 5,358,430 mentioned hereinabove.

As is more readily seen in Figure 2, these two insulation-displacing metallic contacts 1, 2 are each constituted by two thicknesses of metal and are maintained in the rear plastic body 3 of the socket. These insulation-displacing contacts may, of course, each be constituted by a single thickness of metal.

Like the one of US Patent 5,358,430, this socket presents a rotating connection pusher 4 made of plastics material which is in the form of a pivoting cover, this pusher 4 rotating about an axis 5 parallel to the row of insulation-displacing contacts 1, 2.

In Figure 1, the two pairs of pusher-blades 61, 62 and 63, 64 are clearly distinguished, which, when the pivoting cover will be closed, will drive the wires to be connected in their receiving insulation-displacing slots of metallic contact 1 and metallic contact 2, respectively.

By way of illustration, Figure 1 shows a wrapped telephone wire 6 which is placed in position in the contact 1, at the inlet of its second insulation-displacing slot, and which is

therefore ready to be connected by closure of the rotating connection pusher 4.

According to the invention, the pivoting cover, or rotating pusher 4 comprises an elastic end-of-stroke locking catch 7, this catch 7 cooperating with a fixed end-of-stroke locking stop 8. This stop 8 is formed by a prominent beak made of plastics material, which forms part of the body 3 and is obtained by moulding therewith.

As will now be shown with reference to Figures 2 to 5 which illustrate the functioning thereof in detail, the locking stop 8 cooperates, upon closure of the pivoting cover 4, with the elastic catch 7 to create a hard point of passage which corresponds to a maximum tension of this catch and, immediately after passage of this hard point, suddenly to release this catch 7 against the nose of the stop 8, producing a clearly audible click which then indicates to the installer that the insulation-displacing connection of the wire 6 is effectively and positively made with absolute certainty.

Figure 2 shows the pivoting cover 4 at the beginning of the phase of closure. At this stage, the elastic catch 7 just rests, without tension, on the base of the convex ramp 81 which is formed at the front of the stop 8 to receive and push this elastic catch 7 progressively rearwards. The elasticity of the latter is due to the fact that it is borne by the free end of a tongue 71 made of plastics material of which the other end is fast with the pivoting cover 4. At this stage, the pusher-blade 62 (Figure 1) has not yet begun its action of driving the wire 6 in its receiving insulation-displacing slot of the metallic contact 1.

According to Figure 3, by continuing the manual action of closure of the pivoting cover 4, the catch 7 is pushed rearwardly by the stop 8, along the convex ramp 81 thereof. The elastic tongue 71 is then curved, as shown, and is therefore

subjected to a high elastic return tension. At this stage, the pusher-blade 62 begins to drive the wire 6 in its receiving insulation-displacing slot of the contact 1 and therefore to strip and connect the wire 6.

5 At the end of ramp 81, there is then passage of a hard point 82, then, according to Figure 4, very brutal release of the elastic tongue 71 and locking of the pivoting cover 4 by clipping (7-8).

10 During this last phase, the pusher-blade 62 causes total and positive insulation-displacing connection of this wire.

15 The sudden release of the tongue 71 after the passage of the hard point 82-7 causes this tongue to strike the front face, i.e. the nose, of the stop 8, very violently. The violent shock of these two hard bodies then causes a clearly audible click which, in accordance with the result expected by the present invention, indicates to the installer that the insulation-displacing connection of the wire 6 is effected positively, therefore with absolute certainty.

20 It should be noted, as clearly shown in Figure 5, that the positive locking of the cover 4 makes it possible to hold the wire 6 well in its position of connection, thanks in particular to a short vertical groove 9 for reception and hold of the wire 6 which is provided, opposite each insulation-displacing slot, in the body 3, as well as to a conjugate short groove 10 which is provided, on the inner face of the pivoting cover 4, to close this groove 9, performing the role of a lid therefor.

The intensity of the click thus produced upon closure of the cover 4 is typically at least equal to 45 decibels A.

30 It goes without saying that the invention is not limited to the embodiment which has just been described. For example, it is also applicable to sockets which, like the one according to US Patent 5,358,430 mentioned hereinabove, present a plurality of closure pushers instead of one. It is likewise

applicable to devices provided with a non-pivoting connection
pusher which is closed for example by translation and not by
rotation. It is generally applied to the connector technology
industry and therefore not solely to the domain of telephone or
5 computer-related connector technology which has been mentioned
here only by way of preferred but non-limiting example.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:-

1. Method for the connection of wrapped wires by driving these wires in receiving insulation-displacing slots, by means of a rotating pusher of the pivoting cover type, characterized in that it consists in providing an elastic element which is fast with the rotating pusher and which is stretched during rotation of this pusher for engagement of these wires in these slots, then which is suddenly released, at the end of stroke of this pusher, so that it violently hits the nose of a hard body which is prominent with respect to the means for holding the metallic contacts with insulation-displacing slots and which is fast with this means, so as to obtain a clearly audible click which indicates to the installer that the insulation-displacing connection is positively effected and whose sound intensity is at least equal to 45 decibels A.
2. Device for carrying out the method according to Claim 1, characterized in that said rotating pusher bears an elastic tongue having a free end which itself bears an end-of-stroke locking catch on a fixed stop, which is fast with the fixed body which contains and maintains the metallic contacts with insulation-displacing slots, and which forms a protuberance clearly prominent with respect to this fixed body, this locking stop and this catch then cooperating to create a hard point of passage which corresponds to a maximum tension of the tongue and, in locking position, suddenly to release this catch against the beak of the protuberance formed by this stop, the nose of this beak then receiving a sudden shock which produces said clearly audible click, the characteristics of the tongue, its catch and the prominent stop being determined so that the intensity of this click is at least equal to 45 decibels A.

3. A method for connection of insulated wires by driving these wires in receiving insulation-displacing slots by means of a rotating pusher of the pivoting cover type substantially as herein described with reference to the accompanying drawings.

4. An apparatus for connection of insulated wires by driving these wires in receiving insulation-displacing slots by means of a rotating pusher of the pivoting cover type substantially as herein described with reference to the accompanying drawings.

DATED this 17th day of April 1997.


POUYET S.A.

Attorney: CAROLINE M. BOMMER
Fellow Institute of Patent Attorneys of Australia
of SHELSTON WATERS

ABSTRACT

This invention relates to a method and device for reliably and positively connecting electric wires in receiving insulation-displacing slots.

The pivoting connection pusher (4) is closed by a locking catch (7) borne by an
5 elastic tongue (71) and cooperating with a fixed closure stop (8). Locking is produced after passage of a hard point and provokes a clearly audible click which indicates to the installer that the insulation-displacing connection of the wire (6) is then positively effected.









FIG. 3







European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 89 30 7742

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. CL5)
D,A	US-A-4062616 (AMP) * column 2, line 47 - line 67; figures 1-9 *	1, 7	H01R9/07
A	US-A-4310208 (CHABIN CORPORATION) * column 6, line 46 - line 63; figures 1-6 *	1, 7	
			TECHNICAL FIELDS SEARCHED (Int. CL5)
			H01R
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 20 SEPTEMBER 1989	Examiner CERIBELLA G.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

2

EPO FORM 1503 (03.82) (P0401)